(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 29 April 2004 (29.04.2004)

PCT

(10) International Publication Number WO 2004/036047 A1

(51) International Patent Classification⁷: 29/10, 25/00

F04C 29/00,

(21) International Application Number:

PCT/GB2003/004330

(22) International Filing Date: 6 October 2003 (06.10.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0223767.5 0322238.7

14 October 2002 (14.10.2002) GB 23 September 2003 (23.09.2003) GB

(71) Applicant (for all designated States except US): THE BOC GROUP PLC [GB/GB]; Chertsey Road, Windlesham, Surrey GU20 6HJ (GB).

(72) Inventors; and


(75) Inventors/Applicants (for US only): HOPE, Mark,

Christopher [GB/GB]; 79 Elmside, New Addington, Croydon, Surrey CR0 9DU (GB). TUNNA, Clive, Marcus, Lloyd [GB/GB]; Pendle Cottage, The Street, Bolney, West Sussex RH17 5QW (GB). UNDERWOOD, Frederick, John [GB/GB]; 3 Bramber Avenue, Storrington, West Sussex RH20 4HZ (GB).

- (74) Agent: BOOTH, Andrew, Steven; The Boc Group Plc, Chertsey Road, Windlesham, Surrey GU20 6HJ (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

(54) Title: ROTARY PISTON VACUUM PUMP WITH WASHING INSTALLATION



(57) Abstract: A pump comprises at least one rotor (1), a stator (5) and a housing (5), the rotor (1) being enclosed by the housing (5). The housing (5) comprises at least one port (2) extending through the housing (5) to enable delivery of a fluid directly onto a surface of the at least one rotor (1).

